
tigefa jekyll Documentation

Release 3.3.0

sugeng tigefa

Apr 18, 2018

Contents

1	Configuration	3
1.1	RADPRESS_TITLE	3
1.2	RADPRESS_DESCRIPTION	3
1.3	RADPRESS_LIMIT	3
1.4	RADPRESS_GA_CODE	3
1.5	RADPRESS Disqus	4
1.6	RADPRESS_HIDE_EMAIL	4
2	_config.yml	5
2.1	default _config.yml setting	5
2.2	jeekyll config	8
3	Indices and tables	9

Contents:

1.1 RADPRESS_TITLE

Set your blog title.

Default: “Radpress”

1.2 RADPRESS_DESCRIPTION

Set your blog description.

Default: “A blogging application for Djangonauts”

1.3 RADPRESS_LIMIT

Set blog entry count in a page.

Default: 5

1.4 RADPRESS_GA_CODE

Set Google Analytics code to enable support.

Default: None

1.5 RADPRESS_DISQUS

Set shortname if you want to enable Disqus comments support.

Default: None

1.6 RADPRESS_HIDE_EMAIL

If you define this variable as “False”, author emails can be visible in RSS or only author name seems.

Default: True

CHAPTER 2

`_config.yml`

```
def some_function():
    interesting = False
    print 'This line is highlighted.'
    print 'This one is not...'
    print '...but this one is.'
```

2.1 default `_config.yml` setting

```
safe: true
lsi: false
pygments: true
simple_search: http://google.com/search
markdown: kramdown
paginate: 10
kramdown:
  extensions:
    - autolink
    - footnotes
    - smart
permalink: /:year/:month/:title.html
relative_permalink: false
url: http://tigefa4u.github.io
#url: http://localhost:2106
#port: 2106
#baseurl: /project-name
name: tigefa4u.Github
timezone: Aisa/Jakarta
# Themes are encouraged to use these universal variables
# so be sure to set them if your theme uses them.
title : tigefa4u.Github
tagline: love Github repositories
author :
```

```
name : sugeng tigefa
email : tigefa@gmail.com
tumblr: tigefa
flickr: tigefa
github : tigefa4u
repository: tigefa4u.github.io
gittip: tigefa
twitter : tigefa_team
facebook: tigefa.team
feedburner : tigefa4ugithub
linkedin: tigefadotinfo
googleplus: tigefa
pinterest: tigefa
bitbucket: tigefa4u
stackoverflow: tigefa

# The production_url is only used when full-domain names are needed
# such as sitemap.txt
# Most places will/should use BASE_PATH to make the urls
#
# If you have set a CNAME (pages.github.com) set your custom domain here.
# Else if you are pushing to username.github.io, replace with your username.
# Finally if you are pushing to a GitHub project page, include the project name at
↳the end.
#
production_url : http://tigefa4u.github.io

# All Jekyll-Bootstrap specific configurations are namespaced into this hash
#
JB :
  version : 0.3.0

  # All links will be namespaced by BASE_PATH if defined.
  # Links in your website should always be prefixed with {{BASE_PATH}}
  # however this value will be dynamically changed depending on your deployment
↳situation.
  #
  # CNAME (http://yourcustomdomain.com)
  #   DO NOT SET BASE_PATH
  #   (urls will be prefixed with "/" and work relatively)
  #
  # GitHub Pages (http://username.github.io)
  #   DO NOT SET BASE_PATH
  #   (urls will be prefixed with "/" and work relatively)
  #
  # GitHub Project Pages (http://username.github.io/project-name)
  #
  #   A GitHub Project site exists in the `gh-pages` branch of one of your
↳repositories.
  #   REQUIRED! Set BASE_PATH to: http://username.github.io/project-name
  #
  # CAUTION:
  #   - When in Localhost, your site will run from root "/" regardless of BASE_PATH
  #   - Only the following values are falsy: ["", null, false]
  #   - When setting BASE_PATH it must be a valid url.
  #     This means always setting the protocol (http|https) or prefixing with "/"
  BASE_PATH : http://tigefa4u.github.io
```

```

# By default, the asset_path is automatically defined relative to BASE_PATH plus
↳ the enabled theme.
# ex: [BASE_PATH]/assets/themes/[THEME-NAME]
#
# Override this by defining an absolute path to assets here.
# ex:
#   http://s3.amazonaws.com/yoursite/themes/watermelon
#   /assets
#
ASSET_PATH : false

# These paths are to the main pages Jekyll-Bootstrap ships with.
# Some JB helpers refer to these paths; change them here if needed.
#
archive_path: /archive.html
categories_path : /categories.html
tags_path : /tags.html
atom_path : /atom.xml
rss_path : /rss.xml

# Settings for comments helper
# Set 'provider' to the comment provider you want to use.
# Set 'provider' to false to turn commenting off globally.
#
comments :
  provider : disqus
  disqus :
    short_name : tigefa
#   livefyre :
#     site_id : 123
#   intensedebate :
#     account : 123abc
#   facebook :
#     appid : 123
#     num_posts: 5
#     width: 590
#     colorscheme: light

# Settings for analytics helper
# Set 'provider' to the analytics provider you want to use.
# Set 'provider' to false to turn analytics off globally.
#
analytics :
  provider : google
  google :
    tracking_id : 'UA-29791208-6'
#   getclicky :
#     site_id :
#   mixpanel :
#     token : '_MIXPANEL_TOKEN_'
#   piwik :
#     baseURL : 'localhost/piwik' # Piwik installation address (without protocol)
#     idsite : '1'                # the id of the site on Piwik

# Settings for sharing helper.
# Sharing is for things like tweet, plusone, like, reddit buttons etc.
# Set 'provider' to the sharing provider you want to use.
# Set 'provider' to false to turn sharing off globally.

```

```
# options ipost sharethis shareholic addthis
sharing :
  provider : shareholic

# Settings for themes with bootswatch.com
# Set 'provider' to the themes provider you want to use.
# Set 'provider' to false to turn sharing off globally.
# Available themes slate cyborg flatly local cerulean simplex readable cosmo journal_
↪ spacelab united
# view all demo themes http://bootswatch.com
# For local browsing without internet please set 'provider' local
themes:
  provider: slate

# Settings for all other include helpers can be defined by creating
# a hash with key named for the given helper. ex:
#
#   pages_list :
#     provider : "custom"
#
# Setting any helper's provider to 'custom' will bypass the helper code
# and include your custom code. Your custom file must be defined at:
#   ./_includes/custom/[HELPER]
# where [HELPER] is the name of the helper you are overriding.
exclude: ["node_modules", "tigefa.jquery.json", "deploy.cmd", "composer.json",
↪ "circle.yml", "README", "iron.json", "bower.json", "params.json", ".coveralls.yml",
↪ ".travis.yml", ".gitignore", ".gitattributes", ".gitmodules", "README.md", "LICENSE
↪ ", "Rakefile", "CHANGELOG.md", "Gemfile", "Gemfile.lock"]
```

2.2 jekyll config

more info about `_config.yml`

<http://jekyllrb.com/docs/configuration/>

CHAPTER 3

Indices and tables

- search